



(1:1)

$\nabla$  Ra 0.8 (✓)  $\swarrow$   $\begin{matrix} +0.2 \\ +0.1 \end{matrix}$   $\searrow$   $\begin{matrix} -0.1 \\ -0.2 \end{matrix}$   
 general tolerances ISO 2768-K

|   |   |            |       |     |            |     |                                  |      |
|---|---|------------|-------|-----|------------|-----|----------------------------------|------|
| Material: 1.4301  | nominal dimension   | over up to | 1     | 6   | 30         | 100 | 300                              | 1000 |
| Adapter WM40 with D=7mm shaft from M4 to M3 internal thread | tolerance   | ±          | 0.05  | 0.1 | 0.3        | 0.5 | 0.8                              | 1.2  |
|   |   |            | Scale |     | Drawn      |     | Denys Sutter                     |      |
| AD  | 5:1<br>(1:1)  |            | Date  |     | 29.04.2014 |     |                                  |      |
| <b>Ferrovac GmbH</b><br>CH-8050 Zurich                      |   |            | Rev.  |     | A          |     | <b>ADWMS7 (M3I)</b><br>sheet 1/1 |      |
|   | THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF FERROVAC GMBH. ANY REPRODUCTION IN PART OR AS WHOLE WITHOUT OUR PERMISSION IS PROHIBITED. |            |       |     |            |     |                                  |      |