



code: HEXKEY-	metric [mm]	imperial [inch]	L: [mm]
-1500	1.5	-	26
-2000	2	-	26
-2500	2.5	-	26
-3000	3	-	26
-4000	4	-	26
-5000	5	-	26
-2381	2.381	3/32	77
-3175	3.175	1/8	77
-3969	3.969	5/32	77
-4763	4.763	3/16	77

$\sqrt{\text{Ra } 0.8}$  (✓)   
  $\swarrow \begin{matrix} +0.2 \\ +0.1 \end{matrix}$    
  $\searrow \begin{matrix} -0.1 \\ -0.2 \end{matrix}$

Material: fully UHV compatible	nominal $\leq 30\text{mm}$ dimensions $> 30\text{mm}$	DIN ISO 2768-f-H DIN ISO 2768-m-K excluding Sym./Runout
Hex Key for Wobblestick	Sym./Runout $> 30\text{mm}$	DIN ISO 2768-H
HEXKEY	formed part dimensions	DIN ISO 2768-f-H
	Scale	Drawn M. Nyirö
	2:1 (1:1)	Date 25.06.2010
		Changed 29.10.21 CS
<b>Ferrovac</b> CH-8050 Zurich	THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF FERROVAC. ANY REPRODUCTION IN PART OR AS WHOLE WITHOUT OUR PERMISSION IS PROHIBITED.	HEXKEY
Rev.	D	A4 sheet 1/1