



$\sqrt{\text{Ra } 0.8}$ (✓) $\begin{matrix} +0.2 \\ +0.1 \end{matrix}$ $\begin{matrix} -0.1 \\ -0.2 \end{matrix}$
 general tolerances ISO 2768-K

| | | | | | | | | | |
|---|--|-------------------|-----------------------|---------------|-----|-----|-----|------|------|
| Material: fully UHV compatible | | nominal dimension | over up to | 1 | 6 | 30 | 100 | 300 | 1000 |
| | | tolerance ± | | 6 | 30 | 100 | 300 | 1000 | 2000 |
| | | | | 0.05 | 0.1 | 0.3 | 0.5 | 0.8 | 1.2 |
| Numbered stage of receptacles for SHOM sample plates | | Scale | Drawn | C. Weiss | | | | | |
| RECOMSTAGE (20H04S) N | | | Date | 12.05.2014 | | | | | |
| | | | Changed | 31.10.2016 CW | | | | | |
| Ferrovac GmbH | | 2:1 | RECOMSTAGE (20H04S) N | | | | | | |
| CH-8050 Zurich | | | A3 sheet 1/1 | | | | | | |
| THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF FERROVAC GMBH. ANY REPRODUCTION IN PART OR AS WHOLE WITHOUT OUR PERMISSION IS PROHIBITED. | | Rev. | B | | | | | | |