



$\sqrt{\text{Ra } 0.8}$  (✓)  $\swarrow +0.2$   $\searrow +0.1$   $\nwarrow -0.1$   $\swarrow -0.2$

|                                   |   |  |  |
|-----------------------------------|---|--|--|
| Material: all UHV compatible      |   | nominal $\leq 30\text{mm}$   | DIN ISO 2768-f-H                       |
|                                   |   | dimensions $> 30\text{mm}$   | DIN ISO 2768-m-K excluding Sym./Runout |
| Dual Shaft Sample Transporter     |   | Sym./Runout $> 30\text{mm}$  | DIN ISO 2768-H                         |
| RMJ40-1000-0050                   |   | formed part dimensions   | DIN ISO 2768-f-H                       |
|                                   |   | Scale  | Drawn L.Jeromin                        |
|                                   |   |  | Date 29.09.2022                        |
|                                   |   | 1:1  | Changed .....                          |
| <b>Ferrovac</b><br>CH-8050 Zurich |   | THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF FERROVAC. ANY REPRODUCTION IN PART OR AS WHOLE WITHOUT OUR PERMISSION IS PROHIBITED. |  |
| Rev.                              | A | RMJ40-1000-0050  |  |
|                                   |   | A4 sheet 1/1   |  |