



bake-out temperatur $\leq 200^{\circ}\text{C}$

- WM40 $\Rightarrow L = \text{linear travel XXXX} + 470\text{mm}$
- WMG40(FC) $\Rightarrow L = \text{linear travel XXXX} + 470\text{mm}$
- MDG40 $\Rightarrow L = \text{linear travel XXXX} + 470\text{mm}$
- RM40 $\Rightarrow L = \text{linear travel XXXX} + 470\text{mm}$
- RMD40 $\Rightarrow L = \text{linear travel XXXX} + 470\text{mm}$
- RMDG40 $\Rightarrow L = \text{linear travel XXXX} + 500\text{mm}$

∇ Ra 0.8 (\checkmark) \swarrow $\begin{matrix} +0.2 \\ +0.1 \end{matrix}$ \searrow $\begin{matrix} -0.1 \\ -0.2 \end{matrix}$
 general tolerances ISO 2768-K

| | | | | | | | |
|---|---|---------|-----------------|-----|-----|------|------|
| Material:KlevoGlas Texo 656-1 L AL/ KlevoMat Texo E-1 | nominal over | 1 | 6 | 30 | 100 | 300 | 1000 |
| Bakeout tent for UHV Suitcase | dimension up to | 6 | 30 | 100 | 300 | 1000 | 2000 |
| | tolerance \pm | 0.05 | 0.1 | 0.3 | 0.5 | 0.8 | 1.2 |
| | Scale | Drawn | O. Adlung | | | | |
| | | Date | 19.09.2015 | | | | |
| | | changed | 24.06.21 CS | | | | |
| Ferrovac GmbH CH-8050 Zurich | THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF FERROVAC GMBH. ANY REPRODUCTION IN PART OR AS WHOLE WITHOUT OUR PERMISSION IS PROHIBITED. | 1:10 | VSN40SBT | | | | |
| Rev. | C | | | | | | |